

Global Security S-911 Bracelet SIM Card Installation instruction

(Preliminary)

Revision	Release date	Content	author
1.0	2009/07/29	Initial release	Travis Xiong

GLOBAL SECURITY TRACKING INC

Introduction

This document describes the SIM card installation procedure used for the Global Security S-911 Bracelet (Namely Bracelet) production unit.

1.0 Preparation before installation of SIM card

1.1 A valid SIM card

A valid SIM (Subscribe Identity Module) card must be provided by the user in order to use the Bracelet. Your local GSM Carrier will be able to provide you a GPRS DATA and voice enabled SIM card.

The SIM card must be a 3V SIM, the bracelet is not compatible with the older 5V version SIM cards.

1.2 Special tools for installation

- (1) 2 special Phillips screwdrivers are needed for the SIM card installation, one is 1.4mm in size and the other is 1.6mm in size.
- (2) 1 long nose pliers (refer to Fig1).



Fig1. 1.6/1.4 mm Phillips screwdrivers and long nose pliers

2.0 SIM card installation steps

- (1) Push **Power on/off** button to turn off the power supply (refer to Fig2).



Fig2. **Power on/off button (RED)**

- (2) Gently push the wristband pin with a 1.6mm size Phillips screwdriver until about 4mm deep until pin comes out of the other end of the wristband. (refer

to Fig3).



Fig3. Push pin out of the wristband

(3) Same operation on the second pin (refer to Fig4).



Fig4. Example of 2 pins sticking out of the wristband

(4) Slowly pull the 2 pins out with long nose pliers (rubber band will also work) and place them somewhere safely so you don't lose them. (refer to Fig5).



Fig5. Pull out the 2 pins with long nose pliers

(5) Gently unscrew and take out the 4 rear case screws with a 1.4mm size Philips screwdriver and place them somewhere safely so you don't lose them. (refer to Fig6).



Fig6. Unscrew 4 rear case screws

(6) Gently open the Bracelet main case (refer to Fig7).
Do not touch the PCB or any component inside. The ESD (Electrostatic Discharge) can damage the unit permanently.



Fig7. Please don't touch the PCB or any components inside.

(7) Fully insert a valid SIM card into the SIM card holder, label-up. You will see the bottom edge of the SIM card firmly contacts the bottom line of the card holder. (refer to Fig8).



Fig8. Fully insert SIM card into the card holder

(8) Close the main case carefully, and gently fix the 4 screws, refer to Fig6 and Fig5.

(9) Reinstall the wristband carefully, and gently push the 2 pins into wristbands to secure, refer to Fig4.